

CLAIMS :

1. A method of verifying symbolic data for loaded
5 modules, comprising:
 reading trace data for a module;
 comparing the trace data with module symbolic data
in a merged symbol file; and
 verifying that the trace data matches the module
10 symbolic data in the merged symbol file based on one or
more predetermined criteria.

2. The method of claim 1, wherein the one or more
predetermined criteria include one or more of a checksum,
15 a timestamp, a fully qualified path, and a segment size.

3. The method of claim 1, wherein the trace data is
read from a trace buffer.

20 4. The method of claim 1, wherein the trace data is
read from a trace file written to a storage device.

5. The method of claim 1, wherein the reading,
comparing and verifying steps are performed dynamically
25 as trace data is written to a trace buffer.

6. The method of claim 1, wherein the reading,
comparing and verifying steps are performed at a remote
time from when the trace data is written to a trace file.

30 7. The method of claim 1, wherein comparing the trace
data with module symbolic data in a merged symbol file
includes comparing a checksum and timestamp in the trace

Docket No. AUS000127US1

data with a checksum and timestamp in the module symbolic data in the merged symbol file.

8. The method of claim 7, wherein comparing the trace
5 data with module symbolic data in a merged symbol file
further includes comparing a fully qualified path in the
trace data with a fully qualified path in the module
symbolic data, if the checksum and timestamp in the trace
data does not match the checksum and timestamp in the
10 module symbolic data or the checksum and timestamp in the
trace data is not available.

9. The method of claim 8, wherein comparing the trace
data with module symbolic data in a merged symbol file
15 further includes comparing a segment length in the trace
data with a segment length in the module symbolic data,
if the fully qualified path in the trace data does not
match the fully qualified path in the module symbolic
data.

20 10. The method of claim 1, wherein the one or more
criteria have an associated priority.

11. The method of claim 10, wherein the one or more
25 criteria include checksum and timestamp, a fully
qualified path, and a segment size, and wherein the
checksum and timestamp has a highest priority and the
segment size has a lowest priority.

30 12. The method of claim 1, wherein the merged symbol
file includes a plurality of module entries and wherein
comparing the trace data with module symbolic data in a
merged symbol file includes identifying a module entry

09613190.071000

Docket No. AUS000127US1

that is a best match with the trace data.

13. The method of claim 12, wherein identifying a module entry that is a best match with the trace data includes
 5 comparing the trace data to each of the plurality of module entries and identifying one of the plurality of module entries as a best match based on which of the one or more criteria is used to verify the module entry.

10 14. The method of claim 1, wherein the trace data includes redundant information identifying a module for each segment of the module.

15 15. The method of claim 1, wherein the redundant information includes at least one of module checksum, module timestamp and module fully qualified path.

16. A method of displaying data for analyzing a performance trace of a computer application, comprising:
 20 reading module trace data from a trace file;
 reading module symbolic data from a symbolic data file;

verifying that the module symbolic data corresponds to the module trace data;
 25 correlating the module symbolic data with the module trace data to generate correlated data; and
 displaying the correlated data.

17. The method of claim 16, wherein the step of
 30 verifying includes:
 comparing the trace data with the module symbolic data; and
 verifying that the trace data matches the module

000127US1-06T960

symbolic data based on one or more predetermined criteria.

19. The method of claim 16, wherein the trace data is read from a trace buffer.

20. The method of claim 16, wherein the trace data is read from a trace file written to a storage device.

22. The method of claim 21, wherein the one or more criteria include checksum and timestamp, a fully qualified path, and a segment size, and wherein the checksum and timestamp has a highest priority and the segment size has a lowest priority.

24. The method of claim 23, wherein identifying a module entry that is a best match with the trace data includes comparing the trace data to each of the plurality of module entries and identifying one of the plurality of module entries as a best match based on which of the one

or more criteria is used to verify the module entry.

26. The method of claim 16, wherein the redundant information includes at least one of module checksum, module timestamp and module fully qualified path.

27. An apparatus for verifying symbolic data for loaded modules, comprising:

A merged symbol file storage device; and

28. The apparatus of claim 27, wherein the one or more
25 predetermined criteria include one or more of a checksum,
a timestamp, a fully qualified path, and a segment size.

30

30. The apparatus of claim 27, wherein the processor reads the trace data, compares the trace data with module symbolic data and verifies that the trace data matches

Docket No. AUS000127US1

criteria have an associated priority.

36. The apparatus of claim 35, wherein the one or more
criteria include checksum and timestamp, a fully
5 qualified path, and a segment size, and wherein the
checksum and timestamp has a highest priority and the
segment size has a lowest priority.

37. The apparatus of claim 27, wherein the merged
10 symbol file includes a plurality of module entries and
wherein the processor compares the trace data with module
symbolic data in a merged symbol file by identifying a
module entry that is a best match with the trace data.

38. The apparatus of claim 37, wherein the processor
15 identifies a module entry that is a best match with the
trace data by comparing the trace data to each of the
plurality of module entries and identifying one of the
plurality of module entries as a best match based on
20 which of the one or more criteria is used to verify the
module entry.

39. The apparatus of claim 27, wherein the trace data
includes redundant information identifying a module for
25 each segment of the module.

40. The apparatus of claim 27, wherein the redundant
information includes at least one of module checksum,
module timestamp and module fully qualified path.

30

41. An apparatus for displaying data for analyzing a
performance trace of a computer application, comprising:

A trace data storage device;

09613190-071000

Docket No. AUS000127US1

A symbolic data storage device; and

A processor coupled to the trace data storage device and the symbolic data storage device, wherein the processor reads module trace data from the trace data storage device, reads module symbolic data from the symbolic data storage device, verifies that the module symbolic data corresponds to the module trace data, correlates the module symbolic data with the module trace data to generate correlated data, and displays the correlated data on a display device.

42. A computer program product in a computer readable medium for verifying symbolic data for loaded modules, comprising:

first instructions for reading trace data for a module;
second instructions for comparing the trace data with module symbolic data in a merged symbol file; and
third instructions for verifying that the trace data matches the module symbolic data in the merged symbol file based on one or more predetermined criteria.

43. The computer program product of claim 42, wherein the one or more predetermined criteria include one or more of a checksum, a timestamp, a fully qualified path, and a segment size.

44. The computer program product of claim 42, wherein the second instructions for comparing the trace data with module symbolic data in a merged symbol file include instructions for comparing a checksum and timestamp in the trace data with a checksum and timestamp in the module symbolic data in the merged symbol file.

09613190-071000

45. The computer program product of claim 44, wherein the second instructions for comparing the trace data with module symbolic data in a merged symbol file further
5 include instructions for comparing a fully qualified path in the trace data with a fully qualified path in the module symbolic data, if the checksum and timestamp in the trace data does not match the checksum and timestamp in the module symbolic data or the checksum and timestamp
10 in the trace data is not available.

46. The computer program product of claim 45, wherein the second instructions for comparing the trace data with module symbolic data in a merged symbol file further
15 include instructions for comparing a segment length in the trace data with a segment length in the module symbolic data, if the fully qualified path in the trace data does not match the fully qualified path in the module symbolic data.

20 47. The computer program product of claim 42, wherein the merged symbol file includes a plurality of module entries and wherein the second instructions for comparing the trace data with module symbolic data in a merged
25 symbol file include instructions for identifying a module entry that is a best match with the trace data.

48. The computer program product of claim 47, wherein the instructions for identifying a module entry that is a
30 best match with the trace data include instructions for comparing the trace data to each of the plurality of module entries and identifying one of the plurality of module entries as a best match based on which of the one

09643490-01000

or more criteria is used to verify the module entry.

49. A computer program product in a computer readable medium for displaying data for analyzing a performance trace of a computer application, comprising:
- first instructions for reading module trace data from a trace file;
 - second instructions for reading module symbolic data from a symbolic data file;
 - third instructions for verifying that the module symbolic data corresponds to the module trace data;
 - fourth instructions for correlating the module symbolic data with the module trace data to generate correlated data; and
 - fifth instructions for displaying the correlated data.